

### **Product information**

# FIRESTOP CP 617 PUTTY PADS

## **Product description**

• A moldable firestop putty designed to help protect electrical outlet boxes, junction boxes, and washer / dryer boxes

## Applications for use

- · Protection of electrical outlet boxes, washer / dryer boxes and junction boxes
- · General gypsum wall assemblies with wood or metal studs
- When two outlets are located within a single stud / cavity or within 24" measured horizontally (not back-to-back unless specified by specific UL approval)

# Advantages

- Applied by hand, no tools required. Pad can be molded without leaving residue on hands
- No electrical conductivity
- Quick and simple to install
- · Can be used for commercial and residential applications
- Asbestos, formaldehyde and LABS free
- Red list compliant
- No oil migration. Putty remains flexible over time
- Excellent adhesion to gypsum, metal and plastic
- Hilti-branded paper has integrated IFU on each pad
- No methylene diisocynate, phthalates, volatile solvents or abestos fibers

### Installation instructions

Hilti Firestop Saving lives

through innovation and education

See Hilti literature or third-party listings for complete application and installation details

Charles Terrer Construction of the second se
CP GIVE PUTTY



Order designation	Sales pack quantity	ltem number
CP 617 6"x7"	20	309760
CP 617 L 7"x7"	20	333583
CP 617 XL 9"x9"	20	373387



Chemical basis	Butyl rubber
Color	Red
Recommended application temperature	32° to 104° F
Storage and transportation temperature range	23° to 104° F
Density	1.6 g/cm <sup>3</sup>
Temperature resistance range	-4° to 140° F
Mold and mildew performance	Class 0 (ASTM G21-96)
Tested in accordance with	UL 263, UL 1479, CAN / ULC-S115, ASTM E814
Surface burning characteristics	Flame spread 15 (ASTM E84) Smoke development 10 (ASTM E84)
LEED v4.1 compliance	Complies with CDPH standard method v1.2-2017
LEED VOC	4.35 g/L
Dimensions (LxWxH)	CP 617 6"x7": 6"x7"x1/8" (15x18x0.3 cm) CP 617 L 7"x7": 7"x7"x1/8" (18x18x0.3 cm) CP 617 XL 9"x9": 9"x9"x1/8" (2x23x0.3 cm)
Package includes	20 pcs per box
Acoustics performance	59 (relates to specific construction) ASTM E90
Shelf life	Not relevant
Curing time	Non-curing









